


Visual Planning Corporation proudly presents

LX Interview Room Digital Recording System. SPEC sheet for the **LX Legacy S-CFPIP** Stereo Picture-in-Picture System (V.P. Code # VPLX1400)



For this and ALL other LX Digital Recording Systems, the Basic Key components are:

- 1 ea. LX Digital Recorder w/Power Supply
- 1 ea. Sony Studio Headphones
- 1 ea. Bose Stereo Powered Speakers w/Power Supply
- 1 ea. Control Console w/Cable; 1 ea. IR Remote w/batteries
- 1 ea. USB Flash Drive; 1 ea. Power Cord, 1 ea. Manual

Complete list of Major Components for the LX-SFPIP Digital Interview Room Recording System are :

- 1 ea. LX Digital Recording System (V.P. Code# VPLX1000)
- 2 ea. LXMHG (V.P.Code#VPLX1310) Microphones with Stereo Pre-Amp/Compressor & 3' Stereo RCA Cable
- 2 ea. LXCA50 (V.P.Code # VPLZ1315) 50' XLR Audio Cable Kits
- 2 ea. LXCMDV (V.P. Code # VPLX1420) 700 Line Color DSP Mini Dome Camera (1.8-12mm) & (9-22mm)
- 2 ea, LXC50 (V.P. Code \$VPLX1425) 50' BNC Video/DC Power Cable kit
- 1 ea. LXAUPS (V.P. Code # VPLX1430) Uninterruptible Power Supply
- 1 ea. LXPM (V.P. Code # VPLX1435) Premium Archival DVD-R Media with case (100 Pack)
- Shipping UPS Insured: Inches: 24x18x12.>25lbs; 18x12x12>18 lbs. & 18x12x12 > 25 lbs.

Optional Accessories: DVD Transcription Kit (for PC); Streaming Audio/Video Interface Kit; Digital Audio recorders; Custom Disguise Microphones & Cameras; Premium Evidence Archival DVD-R Stock;; Magnetic Card Reader; Extended Factory Warranty Plans.

Technical Specifications:

VIDEO:

DVD Recording System DVD/+ R (Not Region specific) Video recording System : MPEG2, Installed memory: 8GB USB Operating System: Linux Direct; Record Resolution : 720 X 480 D **30 frames per second.** Bit Rate: 4MB/sec (2.0 Hour Mode XP High); 2MB/sec (5.5 Hour Mode, SP Standard), 1 MB/sec (8.5 Hour Mode, LP extended); Expandable to up to 136 hour of continuous recording. DVD Burn/Finalize Time: <11 minutes (1.5 hour Recording, SP Standard. Pre-event Recording : 1-3 Minute adjustable. Time/Date Generator: Integral Time/Date/Character Generator Picture-In-Picture Inserter: Integral 1/4 Screen, Record selectable. Over Record Protection : Two Composite Video (BNC) 1.0 Vp-p w/loop through Video Input: NTSC Standard (525 lines,60 fields) also PAL Standard (625 lines,50 fields)

AUDIO:

Audio Sampling: 16 Bit,48Khz; Audio Input: Two: Line Level(RCA) w/loop through; Speaker: Stereo, External, Powered, Headphone Jack: 1/8" Stereo

DISPLAY:

Viewable size Monitor: (Remote) 17" Diagonal w/Protective Glass, Source PIP Selectable, 5" diag. Resistive Touch Screen, Rec Confidence Display Display Type: LCD Active Matrix Flat Panel (TFT) Contrast ratio: 1000:1; Brightness : 300/cd/m2, Fully adjustable Pixel Pitch: 0.264mm, Response Time: <5ms. Filter Type: 3D Comb Filter/Deinterlace.

General:

Dimensions: (WxHxD) 15.3"x13.5"x7.75", Weight: 17 lbs; Power requirement: 120-140 VAC (50/60 Hz); Power Consumption: <42W DC,12V, 3.5A; Warranty: ONE Year parts & Labour; Regulations: I, CB, FCC (A) CE-Emc (LVD) RoHS, TUV-NRTL Manufactured in the USA.

VISUAL PLANNING CORPORATION:

E-mail: info@visualplanning.com and/or ottawa@visualplanning.com

6805 Decarie Blvd. MONTREAL, QC H3W 3E4, Tel.514-739-3116, Fax: 514-739-0085, Toll-Free: T: 800-361-1192, F: 888-563-8730
1716 Woodward Drive, OTTAWA, ON K2C 0P8, Tel.613-563-8727, Fax: 613-563-8730, Toll-Free: T:888-884-5444, F:888-563-8730
Mississauga: T:905-629-7397, Fax: 905-629-3938; **Vancouver, BC:** T: 800-361-1192 Fax: 888-563-8730

Champlain, NY – 1320 Route 9, #3314, 12919, Tel:518-298-8404 Fax: 518-298-2368, Albany, NY :T 518-298-8404,F:518-298-2368
Burlington, NC- 2209 Tucker St. 27215, Tel: 336-228-0188 Fax:336-227-9211